

PTZOPTICS

3G-SDI Box Camera



Model Number: PTEPTZ-ZCAM-G2 https://ptzoptics.com/zcam/

EPTZ ZCAM

The PTZOptics EPTZ ZCAM is a 1080p @ 30fps camera with a 4K image sensor for capturing HD images at short distances. With support for 3G-SDI & IP streaming, this camera is ideal for delivering high definition video signals to broadcast or live streaming applications.

KEY FEATURES

- Panasonic 1/2.5" HD CMOS Sensor
- Full 1920x1080p HD Resolution up to 30 FPS
- 104° Horizontal Field of View
- 2D & 3D noise reduction
- Simultaneous Dual 3G-SDI & High Definition IP Output
- Dual SDI output (Full view / EPTZ view)
- H.264, H.265 & MJPEG IP streaming outputs
- RTMP / RTMPS & RTSP
- AAC Audio encoding over RTSP and RTMP / RTMPS
- Dynamic / Static IP addressing (Hold D-Pad left for 5+ sec to toggle)
- High performance in low light scenarios
- RS-485 & VISCA over IP available for camera control
- Four (4) Std 1/4-20 female threads for camera mounting
- PoE 802.3af (Power over Ethernet) or 12VDC
- 255 Presets
- 5-year warranty



| Camera & Lens | |
|--------------------------|-------------------------------|
| Video Sensor | 1/2.5" CMOS, 8.51 Mega Pixels |
| Frame Rate | 1080p-30/25, 720p-30/25 |
| Focal Length | F=2.8mm |
| Digital Zoom | Up to 8X |
| Field of View | 104° |
| Min Lux | 0.5 Lux at F1.8, AGC ON |
| Shutter Speed | 1/30s – 1/10000s |
| SNR | ≥55dB |
| Vertical Flip & Mirror | Supported |
| Horizontal Angle of View | 42° (tele) – 104° (wide) |
| Vertical Angle of View | 25° (tele) – 72° (wide) |
| Working Environment | Indoor |

| SDI Output 1Full camera viewSDI Output 2EPTZ video feedVideo Output Interface3G-SDI, IP (RTSP / RTMP)Communication InterfaceRS485 VISCA, Pelco-D, Pelco-PBaud Rate2400/4800/9600 bitsPower Supply InterfaceJEITA type Power Adapter (DC in 12V)Physical SpecificationsDimensions (in.)Dimensions (in.)2.8W x 2.4H x 5.6D (6.3 w/ SDI)Dimensions (mm.)72W x 60H x 143D (162 w/ SDI)Camera Weight1.4 lbs. 0.63 kgBox Dimensions (in.)9.5W x 4.625D x 4.3HBox Dimensions (mm.)241.3W x 117.5D x 109HBox Weight2.0 lbs. 0.90 kg | Rear Board Connectors | |
|---|--------------------------------|---------------------------------|
| Video Output Interface3G-SDI, IP (RTSP / RTMP)Communication InterfaceRS485 VISCA, Pelco-D, Pelco-PBaud Rate2400/4800/9600 bitsPower Supply InterfaceJEITA type Power Adapter (DC in 12V)Physical SpecificationsDimensions (in.)Dimensions (in.)2.8W x 2.4H x 5.6D (6.3 w/ SDI)Dimensions (mm.)72W x 60H x 143D (162 w/ SDI)Camera Weight1.4 lbs. 0.63 kgBox Dimensions (in.)9.5W x 4.625D x 4.3HBox Dimensions (mm.)241.3W x 117.5D x 109H | SDI Output 1 | Full camera view |
| Communication InterfaceRS485 VISCA, Pelco-D, Pelco-PBaud Rate2400/4800/9600 bitsPower Supply InterfaceJEITA type Power Adapter (DC in 12V)Physical SpecificationsDimensions (in.)Dimensions (in.)2.8W x 2.4H x 5.6D (6.3 w/ SDI)Dimensions (mm.)72W x 60H x 143D (162 w/ SDI)Camera Weight1.4 lbs. 0.63 kgBox Dimensions (in.)9.5W x 4.625D x 4.3HBox Dimensions (mm.)241.3W x 117.5D x 109H | SDI Output 2 | EPTZ video feed |
| InterfaceRS485 VISCA, Pelco-D, Pelco-PBaud Rate2400/4800/9600 bitsPower Supply InterfaceJEITA type Power Adapter (DC in 12V)Physical SpecificationsDimensions (in.)Dimensions (in.)2.8W x 2.4H x 5.6D (6.3 w/ SDI)Dimensions (mm.)72W x 60H x 143D (162 w/ SDI)Camera Weight1.4 lbs. 0.63 kgBox Dimensions (in.)9.5W x 4.625D x 4.3HBox Dimensions (mm.)241.3W x 117.5D x 109H | Video Output Interface | 3G-SDI, IP (RTSP / RTMP) |
| Power Supply InterfaceJEITA type Power Adapter (DC in 12V)Physical SpecificationsDimensions (in.)2.8W x 2.4H x 5.6D (6.3 w/ SDI)Dimensions (mm.)72W x 60H x 143D (162 w/ SDI)Camera Weight1.4 lbs. 0.63 kgBox Dimensions (in.)9.5W x 4.625D x 4.3HBox Dimensions (mm.)241.3W x 117.5D x 109H | | RS485 VISCA, Pelco-D, Pelco-P |
| Power Supply Interface 12V) Physical Specifications | Baud Rate | 2400/4800/9600 bits |
| Dimensions (in.) 2.8W x 2.4H x 5.6D (6.3 w/ SDI) Dimensions (mm.) 72W x 60H x 143D (162 w/ SDI) Camera Weight 1.4 lbs. 0.63 kg Box Dimensions (in.) 9.5W x 4.625D x 4.3H Box Dimensions (mm.) 241.3W x 117.5D x 109H | Power Supply Interface | |
| Dimensions (in.) 2.8W x 2.4H x 5.6D (6.3 w/ SDI) Dimensions (mm.) 72W x 60H x 143D (162 w/ SDI) Camera Weight 1.4 lbs. 0.63 kg Box Dimensions (in.) 9.5W x 4.625D x 4.3H Box Dimensions (mm.) 241.3W x 117.5D x 109H | | |
| Dimensions (mm.) 72W x 60H x 143D (162 w/ SDI) Camera Weight 1.4 lbs. 0.63 kg Box Dimensions (in.) 9.5W x 4.625D x 4.3H Box Dimensions (mm.) 241.3W x 117.5D x 109H | Physical Specifications | |
| Camera Weight 1.4 lbs. 0.63 kg Box Dimensions (in.) 9.5W x 4.625D x 4.3H Box Dimensions (mm.) 241.3W x 117.5D x 109H | Dimensions (in.) | 2.8W x 2.4H x 5.6D (6.3 w/ SDI) |
| Box Dimensions (in.) 9.5W x 4.625D x 4.3H Box Dimensions (mm.) 241.3W x 117.5D x 109H | Dimensions (mm.) | 72W x 60H x 143D (162 w/ SDI) |
| Box Dimensions (mm.) 241.3W x 117.5D x 109H | Camera Weight | 1.4 lbs. 0.63 kg |
| | Box Dimensions (in.) | 9.5W x 4.625D x 4.3H |
| Box Weight 2.0 lbs 1.0.90 kg | Box Dimensions (mm.) | 241.3W x 117.5D x 109H |
| 2.0 bb. 0.00 kg | Boy Woight | 20 lbs 1000 kg |

WHAT'S IN THE BOX

EPTZ ZCAM Camera Power Adapter PoE Splitter Quick Start Guide